

Imation Product Environmental Sheet



4, 8 mm DDS/DAT Tape Products

Imation Corp. 1 Imation Way Oakdale, MN 55128-3414 Internet: www.imation.com Product Information USA: 1.800.328.9438 1.651.704.4000	International Contacts:		
	<u>Country</u>	<u>Telephone</u>	<u>Email</u>
	France	01.34.35.54.89	techinfofr@imation.com
	Germany	09001.462846	techinfode@imation.com
	Italy	02.2104.3818	infoit@imation.com
	Netherlands	020.654.26.05	techinfofl@imation.com
	Spain	091.382.84.05	productsinformatic@imation.com
	UK	0.1344.862.201	techinfouk@imation.com

DDS/DAT Tape Products, are considered "articles" as defined by the OSHA Hazard Communication Standard [29CFR 1910.1200]. As such, these products are exempt from the Standard and Material Safety Data Sheet requirements. This Product Information Sheet is provided as a resource to our customers.

The following components are found in Imation DDS/DAT Tape Products:

Components	Material	Weight Percent of Product
Plastic Components	Acrylonitrile butadiene styrene (ABS)	10-12
Film Substrate	PET	3-4
Coating	Iron-cobalt alloy magnetic particle	<2
Binder	Combined resin	<1
Metal Parts	Stainless steel	<1

STORAGE CONDITIONS

- Store in a dry area, away from excessive heat, moisture, chemical fumes and magnetic fields.

DISPOSAL

- Imation has conducted Toxic Characteristic Leachate Procedure (TCLP) tests, per the EPA testing protocol for hazardous waste. These Imation Brand products are not considered regulated waste and are within Federal regulatory limits for TCLP.
- Check with state and local regulations before disposal as they may differ from the Federal classification.
- DDS/DAT Tape Products may be landfilled if permissible, recycled or incinerated.
- Product components and packaging comply with European RoHS and WEEE laws.
- Product components and packaging do not contain or use substance groups of level A that are documented in Japan Green Procurement Survey Standardization Initiative.
- Other international disposal or recycling requirements may apply.

TRANSPORTATION

- DDS/DAT Tape Products are not subject to the requirements of Department of Transportation (DOT) 49 CFR, Subchapter C, Hazardous Materials Regulations (HMR), the European ADR/RID Dangerous Goods Regulations, or the Japan Transportation Ministry Dangerous Goods Regulations.
- DDS/DAT Tape Products are not regulated as a Hazardous Material by the International Civil Aviation Organization (ICAO), the International Air Transport Association (IATA) or the International Maritime Dangerous Goods Code (IMDG).

COMBUSTIBLE PROPERTIES

- Combustion temperature of ABS plastic: 650-750^oF (350-400^oC) .
- The ABS plastic is the primary combustible component, which will oxidize in a fire to carbon dioxide, carbon monoxide, and water, with secondary combustion products of carbon (ash), acrylonitrile and hydrogen cyanide. The coatings will oxidize to similar products. (Contains no PVC plastic.)
- Extinguishing Media: Water

Notice: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Imation makes no warranty expressed or implied.